

A 3D rendering of a server rack with three fans. The fans are white with a circular grille and are mounted on a white rack. The background is a light gray, suggesting a server room environment.

GLACIÄR MICRO

**REFRIGERANT DETECTOR FOR
OEM INTEGRATION**

SIMPLY RELIABLE REFRIGERANT GAS DETECTORS

www.samon.se



REFRIGERANT DETECTOR FOR OEM INTEGRATION

GLACIÄR MICRO is a small-format refrigerant gas detector for installation integrated within OEM equipment.

Gases measured are refrigerants including R32, R454x, and R290.

Typical examples include refrigerated display cases and heat pumps.

Designed and built with over 30 years' experience and expertise in refrigeration applications, **GLACIÄR MICRO** is part of **SAMON's GLACIÄR series** of simply reliable gas detectors



GLACIÄR

FEATURES & BENEFITS

- Infrared sensor requires minimal maintenance
- Auto-zero calibration, no baseline drift
- Long lifetime sensor >10 years
- Field-proven refrigerant detection technology
- Modbus RTU over RS485 for simple integration into control systems
- Addressable detectors for multi-sensor installations





MICRO

SAMON
safe monitoring

- **Plug-&-play out-of-the-box installation**
- **No configuration required**
- **Robust design with high ingress protection for use in harsh environments**

- **Operation continuously monitored with diagnostics & indication in the event of fault**
- **Low power consumption <0,4W allows easy integration with existing control devices**

TECHNICAL DATA

Modbus RTU over RS-485	
Modbus	RTU over RS-485 (30V tolerant)
Baud rate	9600, 19200 (default) or 57600
Data bits	8
Parity	None (default), Odd or Even
Stop bits	1 (default) or 2
Power Supply	
Operating voltage	12 VDC +/- 20%
Power consumption	<=25mA
Operating effect, max.	<0,4 W
Wiring	
Cable size	4 cores, 24 AWG
Cable connector	USB C form, waterproof
Dimensions	
Enclosure Size (W×H×D)	56x128x27
Weight	75g
Environmental	
Operating temperature	-20 to 60 °C
Storage temperature	-20 to 60 °C
Humidity	0 to 90 %RH, non-condensing
Enclosure protection	IP65
Enclosure material	ABS 777D, UL 94/V0
Maximum allowed air pressure	60 to 120 kPa
Sensor	
Technology	Infra-red
Gas	R32 / R454x / R290 (more available on request)
Measuring range	0 - 50 %LFL
Performance	
Warm-up time	60 seconds
Measuring range	0 - 50 %LFL
Accuracy	+/- 10%
Response time	T90 <= 30s

Applicable standards

Standards

UL 60335-2-89 (pending)
IEC/UL 61010-1
UL 60335-2-40
CE

